CVWSH06 55" LED Horizontal Touch Screen



Horizontal Touch Panel

Intelligent Touch

Interactive Smart Touch Panel is an intelligence touch control device which is developed at basic of large screen display and infrared touch control technology.The device integrates TV, computer, android system and other function for education, business and public services.

Smooth Touch Support up to 6 point touch writing, smooth and fast feedback.

High Operation System

Build in Windows as operation system.

Multiple Ports Design

Supports VGA, Audio, HDMI, USB, TOUCH, RJ45, RS232 and multichannel preview function.

Unrivaled Quality, Power Saving and Safety

High Quality Assurance, friendly using-experience

 International brand LED HD display panel configured to ensure better display quality and lower power consumption.


Intelligent Releasing and Interaction Integration System.

 Touching the screen to inquire and read any information as you want.lt is very convenient for real-time news released and advertised.

Touch Support, sensitive input identification

• 6 point infrared touch technology links to fast response speed, strong light resistance and drive free features contribute to quite sensitive input identification.

Machine Size Chart- Unit (mm)



Specifications

	Model	CVWSH06
	Screen Size	55' (16:9)
	Backlight / Lightsource	LED
	Resolution (Pixels)	1920 x 1080 pixels
Panel	Brightness (Typical)	350cd/m2
	Contrast Ratio (Typical)	3,000:1
	Viewing Angle (Horizontal/Vertical)	178°/178°
	Response Time (ms)	I 5ms
	Working Temp.	0-50C
	Panel Bit (8 or 10)	8 bit
	Light Life (Typical)	80,000 hours
	Refresh Rate	60Hz
Glass	Tempered Glass	4mm, Tempered Glass
Touch	No. Of Touches	Unlimited
	Positioning Accuracy	More Than 90% of touch area +-2mm
	Touch Technology	IR Touch
	Numbers of Touch	6 Point touch
	Resolution (Points Area Function)	32,767*32,767
	Touch Interface	USB type B
		Windows 1037U/I3/I5/I7, 4G/8G RAM,
	OS Supported	Intel HD Graphic, 500G/128G SSD
	Internal Speaker	5Wx2
	Line Out (Audio Out, 3.5mm)	xl
Audio	Line In (3.5mm)	NA
	MIC (3.5mm)	xl
	Coax Output	xl
	· · · · · · · · · · · · · · · · · · ·	Power
	Power (AC) Input	xl
	Power Switch	xl
	Basic IO	
	VGA Input	NA
Connectivity	VGA Output	xl
	HDMI Input	NA
	HDMI Output	xl
	Display Port	NA
	Slot-in-PC	xl
	OPS Slot	×2(USB 3.0)
		gacy IO
	RF Input & TF Card	xI&xI
	USB Player (Photo,Video)	x2
Control	RS232 Input	NA
	RJ45 Port	xl
	Firmware Update	USB/OTA
	Voltage	100V-240V, 50/60Hz
Power	Typical (Watt)	<130W
	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Mechanical	Overall Dimension	1291.90 x 1118.44mm
	Height	1118.44 x 718.81mm
	Handle	N/A
	Pen Tray	NA
RF	NFC Reader / Writer	NA
OSD	On-Screen Display Languages	Windows Language
	Remote Controller	NA
	Power Cord	x1(1.5m)
	Audio Cable	N/A
Package / Accessory	VGA Cable	N/A
	Quick Start Guide	NA
	User's Manual Electronic File	lx l
	USB Cable for Touch	N/A
		NA
	Touch Pen (Stylus)	
	Certificate	x l
	Windows Licence	Yes
	Embedded anti glare glass	Yes
Optional	Andoid motherboard	Yes
	Slot-in-PC	Yes

Dealer's Stamp

👐 CreateView

. Specification may vary by region, please visit your local stores for details. Actual product's features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.