
# CVBGH-10 LCD 65" SIGNAGE Smart Touch Wall Type



### **Smart Touch Wall Type Signage**

### Intelligent Touch

Interactive Smart Touch Panel is an intelligence touch control device which is developed at basic of large screen display and infrared touch control technology. The device integrates TV, computer, android system and other function for education, business and public services.

### **Smooth Touch**

Support up to 10 people's concurrent touch and writing, smooth and fast feedback.

#### **Dual Operation System**

Build in Android as operation system, Windows as optional accessories.

### **Multiple Ports Design**

Supports VGA, Audio, HDMI, USB, TOUCH, RJ45, RS232 and multichannel preview function.

## Unrivaled Quality, Power Saving and Safety

### High Quality Assurance, friendly using-experience

• International brand LED HD display panel configured to ensure better display quality and lower power consumption.


### Intelligent Releasing and Interaction Integration System.

 Touching the screen to inquire and read any information as you want. It is very convenient for real-time news released and advertised.

### Multi-Touch Support, sensitive input identification

 Multi-point infrared touch technology links to fast response speed, strong light resistance and drive free features contribute to quite sensitive input identification.

### Machine Size Chart- Unit (mm)



### **Specifications**

	Model	CVBGH-10
	Screen Size	65" (16:9)
	Backlight / Lightsource	LCD
	Resolution (Pixels)	1920x1080 pixel
	Brightness (Typical)	350cd/m2
Panel	Contrast Ratio (Typical)	3,000:1
	Viewing Angle (Horizontal/Vertical)	178°/178°
	Response Time (ms)	15ms
	Color Gamut (x% NTSC)	72%
	Panel Bit (8 or 10)  Point Distance	8 bit 0.744 × 0.744mm
	Refresh Rate	60Hz
Glass	Tempered Glass	4mm, Tempered Glass
Touch	No. Of Touches	Unlimited
	Positioning Accuracy	More Than 90% of touch area +-2mm
	Touch Technology	IR Touch
	Numbers of Touch	10 Point Multi-touch
	Visible Area	I436.2mm(H) × 809mm(V)
	Touch Interface	USB type B
	OS Supported	Windows-1037U/I3/I5/I7/(Optional) Android 5.1, 2G RAM
Audio	Internal Speaker	5Wx2
	Line Out (Audio Out, 3.5mm)	NA
	Line In (3.5mm)	xl
_	MIC (3.5mm)	NA
	Coax Output	NA Power
	Power (AC) Input	xl
	Power Switch	xl
	Basic IO	
	VGA Input	NA
	VGA Output	NA
	HDMI Input	NA
Connectivity	HDMI Output	×Ι
	Display Port	хI
	Slot-in-PC	xl
	OPS Slot ×I (USB 3.0) Legacy IO	
	SD & SIM Card	xI&xI
	USB Player (Photo, Video)	x3
	RS232 Input	NA NA
Control	RJ45 Port	xI
	Firmware Update	USB/OTA
Davies	Voltage	100V-240V, 50/60Hz
Power	Typical (Watt)	<220W
Mechanical		
	Dimension (WxHxD) (mm)	1512.2 x 887.2 x 94.47mm
	Dimension With Bracket	NA NA
	Handle	N/A
RF	Pen Tray  NFC Reader / Writer	N/A NA
KF	NPC Reader / Writer	194
OSD	On-Screen Display Languages	English
	Remote Controller	xI
	Power Cord	x1(1.5m)
	Audio Cable	N/A
	VGA Cable	N/A
Package /	Quick Start Guide	×I
Accessory	User's Manual Electronic File	×I
	USB Cable for Touch	N/A
		NA NA
	Touch Pen (Stylus)	
	Certificate	xI
Ossianal	Nano Smart Pen	NA
	Embedded anti glare glass	NA .
Optional	Micro-cross Star	NA 
	Slot-in-PC	Yes
	Embedded Camera	NA

Dealer's Stamp

