
CVBGH-07 LCD 55" SIGNAGE Smart Touch Wall Type



Smart Touch Wall Type Signage

Intelligent Touch

Interactive Smart Touch Panel is an intelligence touch control device which is developed at basic of large screen display and infrared touch control technology. The device integrates TV, computer, android system and other function for education, business and public services.

Smooth Touch

Support up to 10 people's concurrent touch and writing, smooth and fast feedback.

Dual Operation System

Build in Android as operation system, Windows as optional accessories.

Multiple Ports Design

Supports VGA, Audio, HDMI, USB, TOUCH, RJ45, RS232 and multichannel preview function.

Unrivaled Quality, Power Saving and Safety

High Quality Assurance, friendly using-experience

• International brand LED HD display panel configured to ensure better display quality and lower power consumption.


$\label{ligent Releasing and Interaction Integration} \begin{subarray}{c} \textbf{Intelligent Releasing and Interaction Integration} \\ \textbf{System.} \end{subarray}$

 Touching the screen to inquire and read any information as you want. It is very convenient for real-time news released and advertised.

Multi-Touch Support, sensitive input identification

 Multi-point infrared touch technology links to fast response speed, strong light resistance and drive free features contribute to quite sensitive input identification.

Machine Size Chart- Unit (mm)



Specifications

Screen Size 55" (16:9)	
Backlight / Lightsource LCD	
Brightness (Typical) 350cd/m2	
Contrast Ratio (Typical) 4,000:1	
Panel Viewing Angle (Horizontal/Vertical) 178°/178° Response Time (ms) 15ms Color Gamut (x% NTSC) 72% Panel Bit (8 or 10) 8 bit Point Distance 0.21 x 0.63mm Refresh Rate 60Hz Glass Tempered Glass 4mm, Tempered Glass	
Response Time (ms) 15ms	
Color Gamut (x% NTSC) 72%	
Panel Bit (8 or 10) 8 bit	
Point Distance 0.21 x 0.63mm Refresh Rate 60Hz Glass Tempered Glass 4mm, Tempered Glass	
Refresh Rate 60Hz Glass Tempered Glass 4mm, Tempered Glass	
Glass Tempered Glass 4mm, Tempered Glass	
No. Of Touches Unlimited	
Positioning Accuracy More Than 90% of touch area +-2mr	n
Touch Technology IR Touch	
Touch Numbers of Touch 10 Point Multi-touch	
Visible Area 1213.76mm(H) × 684.36mm	ı(V)
Touch Interface USB type B	
OS Supported Windows-1037U/13/15/17/(Optional Android 5.1, 2G RAM)
Internal Speaker 5Wx2	
Line Out (Audio Out, 3.5mm)	
Audio Line In (3.5mm) xl	
MIC (3.5mm) NA	
Coax Output NA AC Power	
Power (AC) Input x1	
Power Switch x1	
Basic IO	
VGA Input NA	
VGA Output NA	
HDMI Input NA	
Connectivity HDMI Output x1	
Display Port x1	
Slot-in-PC x1	
OPS Slot XI (USB 3.0)	
Legacy IO SD & SIM Card xi & xi	
USB Player (Photo, Video) x3	
RS232 Input NA	
Control RJ45 Port x1	
Firmware Update USB/OTA	
Voltage 100V-240V, 50/60Hz	
Power Typical (Watt) <180W	
Dimension (WxHxD) (mm) 1291.9 x 762.5 x 94.47mr	n
Mechanical Dimension With Bracket N/A	
Handle N/A	
Pen Tray N/A RF NFC Reader / Writer N/A	
NI INIC Reader / Whitei	
OSD On-Screen Display Languages English	
Remote Controller x1	
Power Cord ×I(I.5m)	
Audio Cable N/A	
VGA Cable N/A	
Package / Ouick Start Guide	
Accessory User's Manual Electronic File x1	
USB Cable for Touch N/A	
Touch Pen (Stylus) NA	
Certificate x1	
Nano Smart Pen NA	
Embedded anti glare glass NA	
Optional Micro-cross Star NA	
Slot-in-PC Yes	
Embedded Camera NA	

Dealer's Stamp

